



DURA-ANTIQUÉ RELEASE

DESCRIPTION AND BASIC USE: Proline DURA-ANTIQUÉ RELEASE is used as a bond breaker in the stamping process. It is a dust-on powder with water repellant properties that helps prevent wet concrete from adhering to the polyurethane texture mat. Proline DURA-ANTIQUÉ RELEASE is also used as a coloring agent, leaving a portion of the color, usually darker than the concrete color, imbedded in the low points of the newly textured concrete. This product should be broadcast in thin, even coats that overlap just enough to produce a uniform layer on the slab surface. Release powder can be thrown by hand or with a 6" mason's brush. Stamping can begin as soon as the release agent is applied. Allow concrete to cure for at least 24 hours before removal to prevent damage to the brand new surface. Removal is accomplished by brushing then rinsing with a garden hose spray nozzle, light pressure wash, scrubbing, or buffing. Remove only enough to achieve desired antique effect. Final color that matches the color chart can only be seen by sealing with a quality concrete sealer such as PROLINE High Gloss DURA-SEAL.

BENEFITS: Proline DURA-ANTIQUÉ RELEASE is an easy to use powder with stamp release capabilities. It is offered in 40 standard colors to enhance any decorative concrete surface. DURA-ANTIQUÉ RELEASE is made with stable U.V. resistant, streak-free, iron oxide pigments.

COVERAGE: One 30 pound bucket of Proline DURA-ANTIQUÉ RELEASE covers approximately 1000 square feet. The rate may vary slightly, but will be in the range of 3 to 4 pounds per 100 square feet.

SEALING AND MAINTENANCE: A quality Proline sealer is recommended to protect the newly colored concrete surface. The concrete must be cleaned and thoroughly dried prior to application. Proline provides sealing products such as, DURA-SEAL HG (High Gloss finish) and DURA-SEAL MATTE (Matte finish), which are solvent-based acrylic clear sealers. Inspect annually for areas of thin or traffic-worn sealer and re-apply as necessary. Standard cleaning practices for colored concrete should be followed; schedule periodic cleaning to avoid accumulation of dirt, flatwork and floors are easily maintained by sweeping, clean spills when they occur, hose off dirt with water, and treat heavily soiled areas by wet mopping and/or scrubbing with a properly diluted, high-quality commercial grade detergent.

NOTES: Experimentation of colors and application methods is recommended, as the color of the actual product may differ. Test sections must be produced on each concrete surface. Even in a controlled environment, cements, aggregates, water content, and concrete curing methods will contribute to different results. Final color approval should be made with actual material and sealer selection; however, variation of even mock-up samples due to reproduction limitations should be expected.

CAUTION: KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Use only with adequate ventilation and use a respirator when exposure levels are above applicable limits.

WARRANTY: This product is not for public use and is intended for use by licensed contractors, experienced and trained in the use of these products. It is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.